

DIAMOND TOOL POLISHING MACHINE MODEL DTP-300AX

This diamond tool polishing machine is used to grind and polish single crystal diamond and CVD diamond tools and to process flank face and rake face of single crystal diamond tools.



MODEL DTP-300AX


Even though the upper surface of the scaife is rotating at high speed, extremely runout is small, and accurate surface processing and cutting of the cutting edge of the single crystal diamond tool can be performed.

Polished diamond tool





- Ultra precision air bearing is carried in the body of the foundry structure with increased absorbability.
- The special polishing equiment is carried. Attach the diamond tool to be machined to the work holding tool of the equipment
- ■A portal modification device of a gate type structure is equipped for turning mechanism and grinding mechanism.



Correction of scaife top surface by grinding wheel

- Since the upper surface of the scaife is rotary ground with a grindstone, a smooth polished surface can be obtained.
- Beginners can also rep polish the rake face and flank face of single crystal diamond tool.

Standard specification:

Air bearing with air clean unit Special polishing equipment, 1 unit Scaife correction system 1unit Scaife, 1ps

Special accessories:

Diamond wheel **Dust collector**

SPECIFICATIONS of DTP-300AX

Scale size Φ250~310mm Main spindle rotation speed300~3000r.p.m.
Main spindle rotation speed300∼3000r.p.m.
Main spindle motor(Three phase, 200V,50/60Hz) 750W
Electric powerThree phase, 200V, 50/60Hz
Net weightApprox.750Kgs

Specifications subject to change without notice.

1408251



http://www.imahashi.net

Head office & Factory Postal code 400-0862 3-10-5 Asake, Kofu-shi, Yamanashi-ken, Japan Phone:+81 055 232 3143 Fax:+81 055 232 3149 Email:kofu@imahashi.net

Tokvo office

Postal code 184-8533 Postal Gue 164-6533 In KOGANEI Co., Ltd. 3-11-28 Midori-cho, Koganei-shi, Tokyo Phone: +81 042 383 5517 Fax:+81 042 383 5518 Email:tokyo@imahashi.net